

PART I – GENERAL

KIT DESCRIPTION

Your PortaFloor rollable event flooring kit should contain the following:

1. The amount of flooring purchased.
2. *PortaFloor EX — Rollable Event Flooring Quick Specifications.*
3. *PortaFloor EX SSC — Rollable Event Flooring Installation and Maintenance Guide.*

ACCESSORIES AND OPTIONS

1. PortaFloor Ramp Edge
2. PortaFloor Deploy Cart
3. PortaFloor Pipe EX/SSC 4 ft. wide, 6" diameter, schedule 40
4. PortaFloor Detach Tool
5. Storage Straps 1 in. x 15 ft. with buckle
6. Tile Shear Trimmer

QUALITY ASSURANCE

1. PortaFloor rollable event flooring must be installed according to the manufacturer's instructions in the *PortaFloor EX SSC — Rollable Event Flooring Installation and Maintenance Guide.*
2. PortaFloor rollable event flooring should be site-conditioned at ambient temperatures prior to installation. See the *PortaFloor EX SSC — Rollable Event Flooring Installation and Maintenance Guide* for instructions.
3. Manufacturer is ISO 9001:2008 and ISO 14001:2004 Certified.
4. Manufacturer is a Zero Waste company.

PART II - PRODUCT

DESCRIPTION

1. Perforated top design in modular rollout interlocking tread pieces. Each tread is 12 in. x 3.5 in. x 5/8 in. (30 cm x 9 cm x 1.65 cm) high impact polypropylene copolymer suspended modules with under tile support structure.
2. Individual tile weight: 3.88 oz. (110 grams).
3. The tiles have a built-in positive locking mechanism. Individual treads interconnect on every edge to form a continuous installation of any desired size. Long edge connections are a tab and slot and serve as a living hinge providing the ability to roll the product up. Short edge connections are a tab and slot connection.
4. Product is shipped in pre-assembled sheets of 48.5 in. x 40 in. (123 cm x 101.6 cm) stacked flat on pallets.
5. PortaFloor rollable event flooring has a five (5) year limited warranty from the manufacturer, Sport Court, Salt Lake City, Utah, U.S.A.

PART III – PHYSICAL PROPERTIES

MATERIAL TEST RESULTS

- A. Rockwell hardness (ASTM D 785): 65 R
- B. Heat deflection @ 66 psi (ASTM D 648): 85°C
- C. Tensile Yield Strength (ASTM D 638): 3,000 psi
- D. Elongation at Yield (ASTM D 638): 5%
- E. Notched Izod (ASTM D 256): No break at 23°C

PRODUCT TEST RESULTS

- A. Friction Test (ASTM C1028) Dry/Wet: 0.73/0.66
- B. Fire Rating: UL 94 HB
- C. Point Load Capabilities:
 - 140614 kgf/m²
 - 28800 lbs/ft²
 - 200 psi
- D. Color Consistency: ΔECMC < 1.0 UV stabilized for outdoor use or storage.

SANITARY INFORMATION

Resistance to fungi

1. When tested in compliance with ASTM G-21 and MIL standard 810-D procedure 508.3), all basic organisms tested (ATCC #6205-11797) were found to have zero growth.

Resistance to the following:

1. Bacteria and mildew resistance
2. Gram-positive bacterial Staphylococcus Aureus
3. Gram-negative Klebsiella Pneumoniae
4. Pink-staining organism
5. STV Reticulum
6. Surface fungi growth prior to and following leaching

PART IV – EXECUTION

INSTALLATION

1. PortaFloor rollable event flooring is approved for installation on natural surfaces such as lawns and dirt, and also on synthetic turf, asphalt, gravel, walkways, and floors. For a complete list, contact your local dealer or the manufacturer at 1.800.487.7655 or visit www.portafloor.com.
2. Installation is accomplished by assembling sheets into the desired configuration as provided in the *PortaFloor EX SSC — Rollable Event Flooring Installation and Maintenance Guide*. Tiles can be cut and customized to fit angles such as corners, ovals, doorways, etc.

DISASSEMBLY

Instructions for disassembling the flooring are provided in the *PortaFloor EX SSC — Rollable Event Flooring Installation and Maintenance Guide*. Recommended maximum storage roll/strip size is 400 sq. ft. See "Storage" below.

MAINTENANCE

Instructions for maintaining the flooring are provided in the *PortaFloor EX SSC — Rollable Event Flooring Installation and Maintenance Guide*. For the most recent copy, contact the manufacturer at 1.800.487.7655 or visit www.portafloor.com.

STORAGE

1. While PortaFloor rollable event flooring is not affected by moisture, Sport Court recommends that it be stored in a secure, clean and dry location.
2. If PortaFloor rollable event flooring is stored in rolls, Sport Court requires using 4' wide, 6" diameter pipe with a maximum of 400 square feet of product per roll.
3. Damage to the flooring may be caused by improper storage. To prevent damage, rolls may be stacked horizontally as follows:

<u>Rolls in Feet</u>	<u>Rolls in Centimeters</u>	<u># of Rolls Stacked</u>
4 x 100	123 x 3048	2

Sport Court utilizes only certified laboratories for testing recognized by the following standards and organizations: ANSI, CSA, ASTM, NFPA, ASQC, IAPMO, ISO
www.portafloor.com