

**PART I – GENERAL**

**KIT DESCRIPTION**

Your PortaFloor rollable event flooring kit should contain the following:

1. The amount of flooring purchased.
2. *PortaFloor PRO — Rollable Event Flooring Quick Specifications.*
3. *PortaFloor PRO — Rollable Event Flooring Installation and Maintenance Guide.*

**ACCESSORIES AND OPTIONS**

1. PortaFloor Ramp Edge
2. PortaFloor Pro Pipe 4 ft. wide, 22" OD
3. PortaFloor Detach Tool
4. Storage Straps 1 in. x 15 ft. with buckle
5. Tile Shear Trimmer

**QUALITY ASSURANCE**

1. PortaFloor rollable event flooring must be installed according to the manufacturer's instructions in the *PortaFloor PRO — Rollable Event Flooring Installation and Maintenance Guide.*
2. PortaFloor rollable event flooring should be site-conditioned at ambient temperatures prior to installation. See the *PortaFloor PRO — Rollable Event Flooring Installation and Maintenance Guide* for instructions.
3. Manufacturer is ISO 9001:2008 and ISO 14001:2004 Certified.
4. Manufacturer is a Zero Waste company.

**PART II - PRODUCT**

**DESCRIPTION**

1. Solid top design in modular rollout interlocking tread pieces. Each tread is 24 in. x 6 in. x 15/16 in. (61 cm x 15 cm x 2.4 cm) high impact polypropylene copolymer suspended modules with under tile support structure.
2. Individual tile weight: 1.35 lbs. (612 grams).
3. The tiles have a built-in positive locking mechanism. Individual treads interconnect on every edge to form a continuous installation of any desired size. Long edge connections are a pivot-rod clamp hinge providing the ability to roll the product up. Short edge connections are a tab and slot connection.
4. Product is shipped in pre-assembled sheets of 48 in. x 36 in. (122 cm x 91.4 cm) stacked flat on pallets.
5. PortaFloor rollable event flooring has a five (5) year limited warranty from the manufacturer, Sport Court, Salt Lake City, Utah, U.S.A.

**PART III – PHYSICAL PROPERTIES**

**MATERIAL TEST RESULTS**

- A. Rockwell hardness (ASTM D 785): 65 R
- B. Heat deflection @ 66 psi (ASTM D 648): 85°C
- C. Tensile Yield Strength (ASTM D 638): 3,000 psi
- D. Elongation at Yield (ASTM D 638): 5%
- E. Notched Izod (ASTM D 256): No break at 23°C

**PRODUCT TEST RESULTS**

- A. Friction Test (ASTM C1028) Dry/Wet: 0.91/0.63
- B. R-Value (ASTM C 518): 1.00 h<sup>2</sup>ft<sup>2</sup>°F<sup>2</sup>Btu<sup>-1</sup>
- C. Fire Rating: UL 94 HB
- D. Point Load Capacity:  
168736 kgf/m<sup>2</sup>  
34560 lbs/ft<sup>2</sup>  
240 psi
- E. Color Consistency: ΔECMC < 1.0 UV stabilized for outdoor use or storage.

**SANITARY INFORMATION**

*Resistance to fungi*

1. When tested in compliance with ASTM G-21 and MIL standard 810-D procedure 508.3, all basic organisms tested (ATCC #6205-11797) were found to have zero growth.

*Resistance to the following:*

1. Bacteria and mildew resistance
2. Gram-positive bacterial Staphylococcus Aureus
3. Gram-negative Klebsiella Pneumoniae
4. Pink-staining organism
5. STV Reticulum
6. Surface fungi growth prior to and following leaching

**PART IV – EXECUTION**

**INSTALLATION**

1. PortaFloor rollable event flooring is approved for indoor or outdoor dirt, turf, ice, asphalt, and concrete surfaces. For a complete list, contact your local dealer or call 1.800.487.7655 or visit [www.portafloor.com](http://www.portafloor.com).
2. Installation is accomplished by assembling sheets into the desired configuration as provided in the *PortaFloor PRO — Rollable Event Flooring Installation and Maintenance Guide*. Tiles can be cut and customized to fit angles such as corners, ovals, doorways, etc.

**DISASSEMBLY**

Instructions for disassembling the flooring are provided in the *PortaFloor PRO — Rollable Event Flooring Installation and Maintenance Guide*. Recommended maximum storage roll/strip size is 400 sq. ft. See "Storage" below.

**MAINTENANCE**

Instructions for maintaining the flooring are provided in the *PortaFloor PRO — Rollable Event Flooring Installation and Maintenance Guide*. For the most recent copy, contact your local dealer or call 1.800.487.7655 or visit [www.portafloor.com](http://www.portafloor.com).

**STORAGE**

1. While PortaFloor rollable event flooring is not affected by moisture, Sport Court recommends that it be stored in a secure, clean and dry location.
2. If PortaFloor rollable event flooring is stored in rolls, Sport Court requires using 4' wide, 22" diameter pipe with a maximum of 400 square feet of product per roll.
3. Damage to the flooring may be caused by improper storage. To prevent damage, rolls may be stacked horizontally as follows:

<u>Rolls in Feet</u>	<u>Rolls in Centimeters</u>	<u># of Rolls Stacked</u>
4 x 100	122 x 3048	2